

1932EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

| | | |
|---------------------------|----------------------|-------------|
| Working Height | 25 ft | 7.6 m |
| Raised Platform Height | 19 ft | 5.8 m |
| Lowered Platform Height | 39 in | 0.99 m |
| Platform Size (inside) | 26 x 64 in | 0.7 x 1.6 m |
| Platform Capacity | 550 lbs | 272 kg |
| Overall Width | 32 in | 0.81 m |
| Overall Length | 89 in | 2.26 m |
| Stowed Height | 80.5 in | 1.9 m |
| Deck Extension | 3 ft | 0.91 m |
| Ground Clearance (Stowed) | 2.375 in | 6 cm |
| Ground Clearance (Raised) | 0.7 in | 1.8 cm |
| Wheelbase | 55 in | 1.4 m |
| Inside Turning Radius | Zero | |
| Outside Turning Radius | 66 in | 1.7 m |
| Drive Speed (Stowed) | 1 mph | 1.6 km/h |
| Drive Speed (Raised) | 0.7 mph | 1.1 km/h |
| Batteries | 4 x 6V 250 Amp-hr | |
| Charger | 20 Amp Automatic SCR | |

Specifications Subject to Change



SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class I, Division 1, Group D

STANDARD EQUIPMENT

- 19 ft Platform Height
- 25 ft Working Height
- 26 x 64 in Platform Size
- 2.375 in Ground Clearance
- 550 lb Platform Capacity
- 3 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

OPTIONS

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform