

2032EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	26 ft	7.9 m
Raised Platform Height	20 ft	6.1 m
Lowered Platform Height	38 in	0.97 m
Platform Size (inside)	28 x 84 in	0.7 x 2.1 m
Platform Capacity	900 lbs	408 kg
Overall Width	32 in	0.8 m
Overall Length	108 in	2.75 m
Stowed Height	77.5 in	2.0 m
Deck Extension	3 ft	0.91 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	0.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	50 in	
Outside Turning Radius	108 in	2.7 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h
Batteries	4 x 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications Subject to Change



SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class I, Division 1, Group D

STANDARD EQUIPMENT

- 20 ft Platform Height
- 26 ft Working Height
- 28 x 84 in Platform Size
- 3.5 in Ground Clearance
- 900 lb Platform Capacity
- 3 ft Extendable Deck
- 300 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

OPTIONS

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- 6 ft Powered Extendable Deck