

2632EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	32 ft	9.8 m
Raised Platform Height	26 ft	7.9 m
Lowered Platform Height	45 in	1.1 m
Platform Size (inside)	28 x 84 in	0.7 x 2.1 m
Platform Capacity	500 lbs	227 kg
Overall Width	32 in	0.8 m
Overall Length	108 in	2.75 m
Stowed Height	84.7 in	2.2 m
Deck Extension	3 ft	0.92 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	0.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	50 in	1.3 m
Outside Turning Radius	108 in	2.7 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h
Batteries	4 x 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications Subject to Change



SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class I, Division 1, Group D

STANDARD EQUIPMENT

- 26 ft Platform Height
- 32 ft Working Height
- 28 x 84 in Platform Size
- 3.5 in Ground Clearance
- 500 lb Platform Capacity
- 3 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

OPTIONS

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform