

3246EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	38 ft	11.6 m
Raised Platform Height	32 ft	9.8 m
Lowered Platform Height	48.5 in	1.2 m
Platform Size (inside)	42 x 84 in	1.1 x 2.1 m
Platform Capacity	700 lbs	318 kg
Overall Width	46 in	1.2 m
Overall Length	108 in	2.75 m
Stowed Height	88 in	2.2 m
Deck Extension	4 ft	1.2 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	0.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	47.5 in	1.2 m
Outside Turning Radius	93.5 in	2.4 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.6 mph	1 km/h
Batteries	4 x 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications Subject to Change



SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class I, Division 1, Group D

STANDARD EQUIPMENT

- 32 ft Platform Height
- 38 ft Working Height
- 42 x 84 in Platform Size
- 3.5 in Ground Clearance
- 700 lb Platform Capacity
- 4 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

OPTIONS

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform