

MVL16EX EXPLOSION PROOF VERTICAL MAST LIFT

SPECIFICATIONS

Working Height	21 ft 7 in	6.58 m
Raised Platform Height	15 ft 7 in	4.75 m
Maximum Drive Height	15 ft 7 in	4.75 m
Platform Size	29 x 41 in	.74 x 1.04 m
Platform Capacity	500 lbs	227 kg
Overall Width	30 in	0.76 m
Overall Length	82 in	2.08 m
Stowed Height	64.75 in	1.64 m
Ground Clearance (Stowed)	2.1 in	5.33 cm
Ground Clearance (Raised)	0.63 in	1.60 cm
Inside Turning Radius	Zero	
Outside Turning Radius	55 in	1.40 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h
Batteries	4 x 6V 250 Amp-hr	
Charger	19 Amp Automatic	

Specifications Subject to Change



SAFETY

- Built in Accordance with Class 1, Division 1, Group D

STANDARD EQUIPMENT

- 15 ft 7 in Platform Height
- 21 ft 7 in Working Height
- 29 x 41 in Platform Size
- 2.1 in Ground Clearance
- 500 lb Platform Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Movement Alarm
- 250 Amp Hr Battery

OPTIONS

- Flashing Amber Beacon
- 3/8" Airline to Platform
- Saloon Style Gate